Asir OpenXM-Contrib

Asir OpenXM-Contrib User's Manual (English Edition)
Edition 1.1.2 for OpenXM/Asir2000
February 2000

by OpenXM Developing Team

1 Introduction

The computer algebra system `asir` can use servers, which support the `OpenXM` protocols, as plugin modules. The interface functions to call these servers are read by loading the file '`xm`'. This document explains these interface functions for `asir`.

As to technical details on the `OpenXM` protocols, see '`openxm-eg.tex`' at '`$(OpenXM_HOME)/doc/OpenXM-specs`'.

Enjoy mathematics on your computer.

OpenXM Committers:

- Maekawa, Masahide (Oct., 1999 – : CVS server)
- Noro, Masayuki (Jan., 1996 – : OpenXM Protocol, asir99)
- Ohara, Katsuyoshi (Jan., 1998 – : ox_math)
- Okutani, Yukio (Oct., 1999 – : asir contrib)
- Takayama, Nobuki (Jan., 1996 – : OpenXM Protocol, kan)
- Tamura, Yasushi (Nov., 1998 – : OpenMath proxy)

See `OpenXM/Copyright` for the copyright notice.

2 Function Names in Asir Contrib

Not yet written.

Not yet written.

3 Numbers (Standard Mathematical Functions)

4 Calculus (Standard Mathematical Functions)

5 Series (Standard Mathematical Functions)

6 Hypergeometric Functions (Standard Mathematical Functions)

Not yet written

7 Matrix (Standard Mathematical Functions)

8 Graphic (Standard Mathematical Functions)

9 Print (Standard Mathematical Functions)

10 Polynomials (Standard Mathematical Functions)

11 Complex (Standard Mathematical Functions)

12 OpenMath Function Names

12.0.1 OpenMath CD Basic

`OpenMath Function Names`
:: Asir/OpenXM supports function names in function names following OpenMath Content Dictionaries.

```
Basic_Pi = @pi $
Basic_true = 1$
Basic_false = 0$
Basic_e = @e$
def basic_plus(A,B) { return(A+B); }
def basic_times(A,B) { return(A*B); }
def basic_minus(A,B) { return(A-B); }
def basic_over(A,B) { return(A/B); }
def basic_power(A,B) { return(A^B); }
def basic_and(A,B)   { return(A && B); }
def basic_or(A,B)    { return(A || B); }
def basic_not(A)   { return(! A); }
def basic_IntegerQuotient(A,B) { return(idiv(A,B)); }
def basic_IntegerRemainder(A,B) { return(irem(A,B)); }
def basic_IntegerGcd(A,B)  { return(igcd(A,B)); }
def basic_exp(A)           { return(exp(A)); }
def basic_ln(A)            { return(log(A)); }
def basic_sin(A)           { return(sin(A)); }
def basic_cos(A)           { return(cos(A)); }
def basic_tan(A)           { return(tan(A)); }
def basic_diff(A,B)        { return(diff(A,B)); }
def basic_equal(A,B)       { return( A == B); }
def basic_unequal(A,B)     { return( A != B); }
def basic_less(A,B)        { return( A < B); }
def basic_lessequal(A,B)        { return( A <= B); }
def basic_greater(A,B)        { return( A > B); }
def basic_greaterequal(A,B)        { return( A >= B); }
def basic_select(A,B)         { return(A[B]); }
def basic_length(A)           { if (type(A)==4) return(length(A));
                                else return(size(A)[0]); }
Poly_lexicogrpahic = 2$
Poly_gradedLexicographic = 1$
Poly_gradedReverseLexicographic = 0$
def poly_degreeWrt(A,B)       { return(deg(A,B)); }
def poly_factor(A) { return(fctr(A)); }
def poly_gcd(A,B)  { return(gcd(A,B)); }
def poly_resultant(A,B,V) { return(res(V,A,B)); }
def poly_groebner(O,P,V)  { return(gr(P,V,O)); }
def poly_hilbert_polynomial(I,V,S)  { return(subst(hilbert_polynomial(I,V),h,S)); }
```

It is convinient to have function names without basic_ etc.

```
def factor(F) { return(poly_factor(F)); }
def cancel(F)  { return(red(F)); }
def numerator(F) { return(nm(F)); }
def denominator(F) { return(dn(F)); }
def hilbert_polynomial(G,V) {
     A=gr(G,V,0); B=map(dp_ht,map(dp_ptod,A,V));
     C=map(dp_dtop,B,V);
     return(sm1_hilbert([C,V]));
}
```

13 OpenXM-Contrib General Functions

13.1 Functions

13.1.1 ox_check_errors2

`ox_check_errors2(`*p*`)`
:: get a list of error objects on the statck of the server *p*.

return List

p Number

- It gets a list of error objects on the server stack.
- It does not pop the error objects.

```
[219] P=sm1_start();
0
[220] sm1(P," 0 get ");
0
[221] ox_check_errors2(P);
[error([7,4294967295,executeString: Usage:get])]
Error on the server of the process number = 1
To clean the stack of the ox server,
type in ox_pops(P,N) (P: process number, N: the number of data you need to pop)
out of the debug mode.
If you like to automatically clean data on the server stack,
set XM_debug=0;
```

14 GNUPLOT Functions

This chapter describes interface functions for GNUPLOT ox server `ox_sm1_gnuplot`. These interface functions are defined in the file `gnuplot`. The file '`gnuplot`' is at '`$(OpenXM_HOME)/lib/asir-contrib`'.

```
[nobuki@yama doc]$ asir
This is Asir, Version 991116.
Copyright (C) FUJITSU LABORATORIES LIMITED.
3 March 1994. All rights reserved.
[155] load("xm");
1
xm Version 19991109. ox_help(0); ox_help("keyword"); for help message
[255] gnuplot_start();
0
[257] gnuplot("plot sin(x**2);");
0
```

The function `heat`(dt,*step*) demonstrates our gnuplot interface. It numerically solves the heat equation

$$\frac{\partial u}{\partial t} = \frac{\partial^2 u}{\partial x^2}, \quad u(t,0) = u(t,1) = 1$$

with the initial condition

$$u(0,x) = x, \ (0 \le x \le 0.5), \quad u(1,x) = 1 - x, \ (0.5 \le x \le 1)$$

by the explicit scheme for $0 \le t \le dt * step$. The segment [0,1] is devided into `Heat_N` segments. If the celebrated Courant-Friedrichs-Levi number dt*`Heat_N`*`Heat_N` is less than or equal to 0.5, then the explicit scheme is numerically stable. One can observe the instability by changing CFL number.

```
Heat_N=20; heat(0.001,30);   (CFL number is 0.4)
Heat_N=20; heat(0.003,30);   (CFL > 0.5 unstable)
```

Author of `GNUPLOT`: Thomas Williams, Colin Kelley

14.1 Functions

14.1.1 gnuplot_start

`gnuplot_start()`
:: Start `ox_sm1_gnuplot` on the localhost.

return Integer

- Start `ox_sm1_gnuplot` on the localhost. It returns the descriptor of `ox_sm1_gnuplot`.
- Set `Xm_noX = 1` to start `ox_sm1_gnuplot` without a debug window.
- The descriptor is stored in `Gnuplot_proc`.

```
P = gnuplot_start();
```

`Reference`
`ox_launch`, `gnuplot`

14.1.2 gnuplot

`gnuplot(`*s*`|proc=`*p*`)`
:: Ask GNUPLOT to execute the command string *s*.

return Void

p Number

s String

- The server executes the gnuplot command *s*. When an error occurs, the gnuplot itself terminates and ox_sm1_gnuplot server automatically restarts gnuplot.
- gnuplot does not accept a long polynomial.
- gnuplot does not accept ^. Use ** instead.

```
[232] P = gnuplot_start();
0
*Plot 3 dimensional graph.
[233] gnuplot("splot x**2-y**2;"|proc=P);
0
*Plot 2 dimensional graph.
[234] gnuplot("plot [-pi:pi] [-2:2] cos(x);");
0
*Output a graph as a postscript figure.
[235] gnuplot_output(|file="hoge.eps");
0
[236] gnuplot("plot sin(x)*cos(x);");
0
[237] gnuplot(|file="x11");
0

*Plot 3 dimensional graph hiding unvisible lines.
[236] gnuplot("set hidden3d");
0
[237] gnuplot("splot (x**2+y**2)*sin(x**2+y**2)");
0
[238] gnuplot("set isosamples 50");
0
[239] gnuplot("splot (x**2+y**2)*sin(x**2+y**2)");
```

`Reference`
`ox_launch`, `gnuplot_start`, `rtostr`, `gnuplot_plot_dots`

`Reference Book`
Yabuki Michiro, Otake Tuyoshi; Tukai konasu GNUPLOT, Techno Press, in Japansese, ISBN4-924998-11-7

14.1.3 gnuplot_plot_dots

`gnuplot_plot_dots(`*d*`,`*s*`|proc=`*p*`)`
:: Plot the dots *d* with the style *s*.

return Void

p Number

d List

s String or 0

- Plot the dots *d* with the style *s*. *s* is a string of the form "style color point". Here, style can be lines, points, linespoints, impulses, dots, steps, errorbars, boxes, boxerrorbars. color can be 1 (red), 2 (green), 3 (blue), 4, ... , 8. point can be a number from 1 to 8. The color and point field can be omitted.
- When *d* == [ ], the screen will be cleared.

```
[239] P = gnuplot_start();
0
[240] gnuplot_plot_dots([ ],0);
0
[241] for (I=0; I<10; I++) gnuplot_plot_dots([[I,I^2]]," lines ");
[242] A = [ ];
[]
[243] for (I=0; I<10; I++) A = append(A,[ [I,I^2]]);
[244] A;
[[0,0],[1,1],[2,4],[3,9],[4,16],[5,25],[6,36],[7,49],[8,64],[9,81]]
[245] gnuplot_plot_dots(A," lines ");
0
```

Reference

gnuplot_start, plot "fileName" with options(GNUPLOT command), gnuplot_clean, gnuplot

14.1.4 gnuplot_output

gnuplot_output(|*file*=*s*)

:: ask GNUPLOT to output graphic to the file *s* in the Postscript format.

return Void

s String

- ask GNUPLOT to output graphic to the file *s* in the Postscript format.
- When s is "x11" or this function is called without the argument, the output will be written to X11 display.

```
[273] gnuplot_output(|file="hoge.eps");
Graphic output of GNUPLOT will be written to hoge.eps as a Poscript file.
0
[274] gnuplot("plot tan(x)+sin(x);");
0
[275] gnuplot_output();
Usage of gnuplot_output: gnuplot_output(|file="string")
                         gnuplot_output(|file="x11")
Output device is set to X11
```

Reference

gnuplot

14.1.5 gnuplot_plot_function

`gnuplot(`*f*`|proc=`*p*`)`
:: ask the `gnuplot` server to draw a graph of *f*

return Void

p Number

f Polynomial or a list of polynomials

- ask the `gnuplot` server to draw a graph of *f*

```
[290] gnuplot_plot_function((x+sin(x))^2);
0
[291] gnuplot_plot_function([x,x^2,x^3]);
0
```

`Reference`
`gnuplot_to_gnuplot_format`

15 Mathematica Functions

This chapter describes interface functions for Mathematica ox server `ox_math`. These interface functions are defined in the file 'm'. You need to load the file before using the interface functions. by the command `load("m")$`. The file 'm' is at '`$(OpenXM_HOME)/lib/asir-contrib`'.

Note: `ox_reset` does not work.

```
bash$ asir
This is Asir, Version 991110.
Copyright (C) FUJITSU LABORATORIES LIMITED.
3 March 1994. All rights reserved.
[155] load("m");
1
1
xm Version 19991109. ox_help(0); ox_help("keyword"); for help message
m Version 19991113. m_start, m_tree_to_string, m_N_Eigenvalues
[259] m_start();
ox_math has started.
ox_math: Portions copyright 2000 Wolfram Research, Inc.
See OpenXM/Copyright/Copyright.mathlink  for details.
0
[260] m_N_Eigenvalues([[1,2],[4,5]]);
[-0.464102,6.4641]
```

`Mathematica` is the trade mark of Wolfram Research Inc. This package requires Mathmatica Version 3.0, so you need to buy Mathematica from Wolfram Research to make this package work. See `http://www.wolfram.com`

Author of `ox_math`: Katsuyoshi Ohara, `ohara@air.s.kanazawa-u.ac.jp`.

15.1 Functions

15.1.1 m_start

`m_start()`
:: Start `ox_math` on the localhost.

return Integer

- Start `ox_math` on the localhost. It returns the descriptor of `ox_math`.
- Set `Xm_noX = 1` to start `ox_math` without a debug window.
- The descriptor is stored in the variable `M_proc`.

```
P = m_start()
```

`Reference`
`ox_launch`

15.1.2 m_tree_to_string

`m_tree_to_string(`*t*`)`
:: translates Mathematica tree data *t* into a string that can be understandable by `asir` as far as possible.

return String

t List

- t is a Mathematica tree data which is generated by `ox_math`.
- This function translates Mathematica tree data *t* into a string that may be understandable by `asir`.
- This function translates *t* into a prefix or infix expression that may be understantable by `asir`. The first element of the list *t* is a key word string of the Mathematica object. If this function recognizes the key word, it translates `t` into the form that can be understandable by `asir`. If it cannot recognizes the key word, it translates `t` into a function call with the function name `m_(the key word)`.

```
[267] m_start();
0
[268] ox_execute_string(0,"Expand[(x-1)^2]");
0
[269] A=ox_pop_cmo(0);
[Plus,1,[Times,-2,x],[Power,x,2]]
[270] m_tree_to_string(A);
(1)+((-2)*(x))+((x)^(2))
[271] eval_str(@);
x^2-2*x+1
[259] m_tree_to_string(["List",1,2]);
[1 , 2]
[260] m_tree_to_string(["Plus",2,3]);
(2)+(3)
[261] m_tree_to_string(["Complex",2.3,4.55]);
m_Complex(2.3 , 4.55)
[362] m_tree_to_string(["Plus",["Complex",1.2,3.5],1/2]);
(m_Complex(1.2 , 3.5))+(1/2)
[380] eval_str(@);
(1.7+3.5*)
```

Reference
`ox_pop_cmo`, `eval_str`, `m_rtostr`

15.1.3 m_rtostr

`m_rtostr(`*t*`)`
:: translate the object *t* into a string that can be understandable by Mathematica as far as possible.

return String

t Object

- It translates the object t into a string that can be understandable by Mathematica as far as possible. For example, `asir` uses `[, ]` to express a list, but `Mathematica` uses `{, }`. This function makes this sort of translations.

```
[259] m_rtostr([1,2,3]);
1,2,3
[260] m_rtostr([[1,x,x^2],[1,y,y^2]]);
{{1,x,x^2},{1,y,y^2}}
```

Let us see one more example. The following function `m_Inverse(M)` outputs the inverse matrix of the matrix `M` by calling `ox_math`. It translates `asir` matrix `M` into a Mathematica expression by `r_tostr(M)` and makes Mathematica compute the inverse matrix of `M` by `ox_execute_string`.

```
def m_Inverse(M) {
  P = 0;
  A = m_rtostr(M);
  ox_execute_string(P,"Inverse["+A+"]");
  B = ox_pop_cmo(B);
  C = m_tree_to_string(B);
  return(eval_str(C));
}

[269] M=[[1,x,x^2],[1,y,y^2],[1,z,z^2]];
[[1,x,x^2],[1,y,y^2],[1,z,z^2]]
[270] A=m_Inverse(M)$
[271] red(A[0][0]);
(z*y)/(x^2+(-y-z)*x+z*y)
```

Reference

`ox_execute_string`, `ToExpression`(Mathematica), `m_tree_to_string`

16 OpenMath Functions

In order to use functions in this section, you need to load `om` by the command `load("om");`

Author of OMproxy : Yasushi Tamura , `tamura.kobe-u.ac.jp`

16.0.1 om_start

`om_start()`
:: Start `OMproxy` server to make a translation between CMO and OpenMath XML expressions.

return Number

```
[155] load("om");
1
[160] om_start();
control: wait OX
Trying to connect to the server... Done.
0
[161] om_xml(<<1,0>>+2*<<0,1>>);
<OMOBJ><OMA><OMS name="DMP" cd="poly"/>
<OMA><OMS name="PolyRing" cd="poly"/>
 <OMI>2</OMI></OMA><OMA>
 <OMS name="SDMP" cd="poly"/>
 <OMA><OMS name="Monom" cd="poly"/><OMI>1</OMI><OMI>1</OMI><OMI>0</OMI></OMA>
 <OMA><OMS name="Monom" cd="poly"/><OMI>2</OMI><OMI>0</OMI><OMI>1</OMI></OMA>
</OMA></OMA></OMOBJ>
[162] om_xml_to_cmo(@);
(1)*<<1,0>>+(2)*<<0,1>>
```

16.0.2 om_xml

`om_xml(`s`|proc=`p`)`
:: Translate CMO expression of s to a XML expression of OpenMath.

return String

p Number

s Object

- Translate CMO s to a XML expression of OpenMath.

```
For (I=0; I<10; I++)
   A = 2^I;
   B = om_xml(A);
   C = om_xml_to_cmo(B);
   print(A == C);
```

16.0.3 `om_xml_to_cmo`

`om_xml_to_cmo(`*s*`|proc=`*p*`)`
:: Translate XML expression *s* of OpenMath to a CMO.

return Object

p Number

s String

- Translate XML expression *s* of OpenMath to a CMO.

17 PHC Functions

This chapter describes interface functions for PHC pack ox server `ox_sm1_phc`. These interface functions are defined in the file 'phc'. The file `phc` is at '`$(OpenXM_HOME)/lib/asir-contrib`'.

```
[nobuki@yama doc]$ asir
This is Asir, Version 991116.
Copyright (C) FUJITSU LABORATORIES LIMITED.
3 March 1994. All rights reserved.
[155] load("xm");
1
xm Version 19991109. ox_help(0); ox_help("keyword"); for help message
[255] phc_start();
0
[257] phc([x^2+y^2-4,x*y-1]);
The detailed output is in the file tmp.output.*
The answer is in the variable Phc.
0
[260] Phc ;
[[[-0.517638,0],[-1.93185,0]],
[[1.93185,0],[0.517638,0]],
[[-1.93185,0],[-0.517638,0]],
[[0.517638,0],[1.93185,0]]]
[261]
```

Author of `PHC pack`: Jan Verschelde.

Reference 1: Jan Verschelde, PHCpack: A general-purpose solver for polynomial systems by homotopy continuation". ACM Transaction on Mathematical Softwares, 25(2): 251-276, 1999.

Reference 2: Cox, D., O'Shea, Little, J., Using Algebraic Geometry, Springer. See the chapter on mixed volumes.

17.1 Functions

17.1.1 phc_start

`phc_start()`
:: Start `ox_sm1_phc` on the localhost.

return Integer

- Start `ox_sm1_phc` on the localhost. It returns the descriptor of `ox_sm1_phc`.
- Set `Xm_noX = 1` to start `ox_sm1_phc` without a debug window.
- The descriptor is stored in `Phc_proc`.

```
P = phc_start()
```

`Reference`
`ox_launch`, `phc`

17.1.2 phc

phc(s|proc=*p*)
:: Ask PHC pack to find all the roots in the complex torus of the given systems of polynomials *s*

return Void

p Number

s List

- The server calls PHC pack to solve a system of algebraic equations S by homotopy methods. PHC pack has been developed by Jan Verschelde. See `www.mth.msu.edu/~jan` for the original distribution. The original PHC pack can choose several strategies to solve, but our phc interface uses only black-box solver, which is general and automatic but is not efficient. So, if you fails by our interface, try the other strategies via the original user interface.
- phc generates working files tmp.phc.out.pid, tmp.input.*, tmp.output.*. Here, pid the process number of the server. The file `tmp.output.*` contains details informations on how PCH pack solves the system.
- The number of variables and the number of equations `length(s)` must agree.

```
[232] P = phc_start();
0
[233] phc([x^2+y^2-4,x*y-1]|proc=P);
The detailed output is in the file tmp.output.*
The answer is in the variable Phc.
0
[234] Phc;
[[[-1.93185,0],[-0.517638,0]],
 [[0.517638,0],[1.93185,0]],
 [[-0.517638,0],[-1.93185,0]],
 [[1.93185,0],[0.517638,0]]]

 [[x=[real, imaginary], y=[real,imaginary]],  the first solution
  [x=[real, imaginary], y=[real,imaginary]],  the second solution
  ...
```

Reference
: `ox_launch`, `phc_start`, '`$(OpenXM_HOME)/bin/lin_phcv2`'(original PHC pack binary for linux)

18 SM1 Functions

This chapter describes interface functions for sm1 ox server `ox_sm1_forAsir`. These interface functions are defined in the file '`sm1`'. The file '`sm1`' is at '`$(OpenXM_HOME)/lib/asir/contrib-packages`'. The system `sm1` is a system to compute in the ring of differential operators. Many constructions of invariants in the computational algebraic geometry reduce to constructions in the ring of differential operators. Documents on `sm1` are in the directory `OpenXM/doc/kan96xx`.

All the coefficients of input polynomials should be integers for most functions in this section. Other functions accept rational numbers as inputs and it will be explicitely noted in each explanation of these functions.

Let us evaluate the dimensions of the de Rham cohomology groups of $X := \mathbf{C} \setminus \{0, 1\} = \mathbf{C} \setminus V(x(x-1))$. The space X is a two punctured plane, so two loops that encircles the points $x = 0$ and $x = 1$ respectively spans the first homology group. Hence, the dimension of the first de Rham cohomology group is 2. `sm1` answers the dimensions of the 0th and the first cohomology groups.

```
This is Risa/Asir, Version 20000126.
Copyright (C) FUJITSU LABORATORIES LIMITED.
1994-1999. All rights reserved.
xm version 20000202. Copyright (C) OpenXM Developing Team. 2000.
ox_help(0); ox_help("keyword"); ox_grep("keyword"); for help message
Loading ~/.asirrc

[283] sm1_deRham([x*(x-1),[x]]);
[1,2]
```

The author of `sm1` : Nobuki Takayama, `takayama@math.sci.kobe-u.ac.jp`
The author of sm1 packages : Toshinori Oaku, `oaku@twcu.ac.jp`
Reference: [SST] Saito, M., Sturmfels, B., Takayama, N., Grobner Deformations of Hypergeometric Differential Equations, 1999, Springer. See the appendix.

18.1 `ox_sm1_forAsir` Server

18.1.1 `ox_sm1_forAsir`

`ox_sm1_forAsir`
:: `sm1` server for `asir`.

- `ox_sm1_forAsir` is the `sm1` server started from asir by the command `sm1_start`. In the standard setting,
  `ox_sm1_forAsir` = '`$(OpenXM_HOME)/lib/sm1/bin/ox_sm1`' + '`$(OpenXM_HOME)/lib/sm1/callsm1.sm1`' (macro file)
  + '`$(OpenXM_HOME)/lib/sm1/callsm1b.sm1`' (macro file)
  The macro files '`callsm1.sm1`' and '`callsm1b.sm1`' are searched from current directory, `$(LOAD_SM1_PATH)`, `$(OpenXM_HOME)/lib/sm1`, `/usr/local/lib/sm1` in this order.

- Note for programmers: See the files '`$(OpenXM_HOME)/src/kxx/oxserver00.c`', '`$(OpenXM_HOME)/src/kxx/sm1stackmachine.c`' to build your own server by reading `sm1` macros.

18.2 Functions

18.2.1 sm1_start

`sm1_start()`
:: Start `ox_sm1_forAsir` on the localhost.

return Integer

- Start `ox_sm1_forAsir` on the localhost. It returns the descriptor of `ox_sm1_forAsir`.
- Set `Xm_noX = 1` to start `ox_sm1_forAsir` without a debug window.
- You might have to set suitable orders of variable by the command `ord`. For example, when you are working in the ring of differential operators on the variable `x` and `dx` (`dx` stands for $\partial/\partial x$), `sm1` server assumes that the variable `dx` is collected to the right and the variable `x` is collected to the left in the printed expression. In the example below, you must not use the variable `cc` for computation in `sm1`.
- The variables from `a` to `z` except `d` and `o` and `x0`, ..., `x20`, `y0`, ..., `y20`, `z0`, ..., `z20` can be used as variables for ring of differential operators in default. (cf. `Sm1_ord_list` in `sm1`).
- The descriptor is stored in `Sm1_proc`.

```
[260] ord([da,a,db,b]);
[da,a,db,b,dx,dy,dz,x,y,z,dt,ds,t,s,u,v,w,
......... omit ..................
]
[261] a*da;
a*da
[262] cc*dcc;
dcc*cc
[263] sm1_mul(da,a,[a]);
a*da+1
[264] sm1_mul(a,da,[a]);
a*da
```

`Reference`
`ox_launch`, `sm1_push_int0`, `sm1_push_poly0`, `ord`

18.2.2 sm1

`sm1(`p`,`s`)` :: ask the `sm1` server to execute the command string s.

return Void

p Number

s String

- It asks the `sm1` server of the descriptor number p to execute the command string s.

```
[261] sm1(0," ( (x-1)^2 ) . ");
0
[262] ox_pop_string(0);
x^2-2*x+1
[263] sm1(0," [(x*(x-1))  [(x)]] deRham ");
0
[264] ox_pop_string(0);
[1 , 2]
```

`Reference`
`sm1_start`, `ox_push_int0`, `sm1_push_poly0`.

18.2.3 sm1_push_int0

`sm1_push_int0(`p`,`f`)`
:: push the object f to the server with the descriptor number p.

return Void

p Number

f Object

- When `type(`f`)` is 2 (recursive polynomial), f is converted to a string (type == 7) and is sent to the server by `ox_push_cmo`.
- When `type(`f`)` is 0 (zero), it is translated to the 32 bit integer zero on the server. Note that `ox_push_cmo(`p`,0)` sends `CMO_NULL` to the server. In other words, the server does not get the 32 bit integer 0 nor the bignum 0.
- `sm1` integers are classfied into the 32 bit integer and the bignum. When `type(`f`)` is 1 (number), it is translated to the 32 bit integer on the server. Note that `ox_push_cmo(`p`,1234)` send the bignum 1234 to the `sm1` server.
- In other cases, `ox_push_cmo` is called without data conversion.

`Reference`
`ox_push_cmo`

18.2.4 sm1_gb

`sm1_gb([`f`,`v`,`w`]|proc=`p`,sorted=`q`)`
:: computes the Grobner basis of f in the ring of differential operators with the variable v.

`sm1_gb_d([`f`,`v`,`w`]|proc=`p`)`
:: computes the Grobner basis of f in the ring of differential operators with the variable v. The result will be returned as a list of distributed polynomials.

return List

p, q Number

f, v, w List

- It returns the Grobner basis of the set of polynomials f in the ring of deferential operators with the variables v.
- The weight vectors are given by w, which can be omitted. If w is not given, the graded reverse lexicographic order will be used to compute Grobner basis.
- The return value of `sm1_gb` is the list of the Grobner basis of f and the initial terms (when w is not given) or initial ideal (when w is given).
- `sm1_gb_d` returns the results by a list of distributed polynomials. Monomials in each distributed polynomial are ordered in the given order. The return value consists of [variable names, order matrix, grobner basis in distriucted polynomials, initial monomials or initial polynomials].
- When a non-term order is given, the Grobner basis is computed in the homogenized Weyl algebra (See Section 1.2 of the book of SST). The homogenization variable h is automatically added.
- When the optional variable q is set, `sm1_gb` returns, as the third return value, a list of the Grobner basis and the initial ideal with sums of monomials sorted by the given order. Each polynomial is expressed as a string temporally for now.

```
[293] sm1_gb([[x*dx+y*dy-1,x*y*dx*dy-2],[x,y]]);
[[x*dx+y*dy-1,y^2*dy^2+2],[x*dx,y^2*dy^2]]
```

In the example above, the set $\{x\partial_x + y\partial_y - 1, y^2\partial_y^2 + 2\}$ is the Gröbner basis of the input with respect to the graded reverse lexicographic order such that $1 \leq \partial_y \leq \partial_x \leq y \leq x \leq \cdots$. The set $\{x\partial_x, y^2\partial_y\}$ is the leading monomials (the initial monominals) of the Gröbner basis.

```
[294] sm1_gb([[dx^2+dy^2-4,dx*dy-1],[x,y],[[dx,50,dy,2,x,1]]]);
[[dx+dy^3-4*dy,-dy^4+4*dy^2-1],[dx,-dy^4]]
```

In the example above, two monomials $m = x^a y^b \partial_x^c \partial_y^d$ and $m' = x^{a'} y^{b'} \partial_x^{c'} \partial_y^{d'}$ are firstly compared by the weight vector `(dx,dy,x,y) = (50,2,1,0)` (i.e., m is larger than m' if $50c + 2d + a > 50c' + 2d' + a'$) and when the comparison is tie, then these are compared by the reverse lexicographic order (i.e., if $50c + 2d + a = 50c' + 2d' + a'$, then use the reverse lexicogrpahic order).

```
[294] F=sm1_gb([[dx^2+dy^2-4,dx*dy-1],[x,y],[[dx,50,dy,2,x,1]]]|sorted=1);
      map(print,F[2][0])$
      map(print,F[2][1])$
[595]
   sm1_gb([["dx*(x*dx +y*dy-2)-1","dy*(x*dx + y*dy -2)-1"],
             [x,y],[[dx,1,x,-1],[dy,1]]]);

[[x*dx^2+(y*dy-h^2)*dx-h^3,x*dy*dx+y*dy^2-h^2*dy-h^3,h^3*dx-h^3*dy],
 [x*dx^2+(y*dy-h^2)*dx,x*dy*dx+y*dy^2-h^2*dy-h^3,h^3*dx]]

[596]
   sm1_gb_d([["dx (x dx +y dy-2)-1","dy (x dx + y dy -2)-1"],
             "x,y",[[dx,1,x,-1],[dy,1]]]);
[[[e0,x,y,H,E,dx,dy,h],
 [[0,-1,0,0,0,1,0,0],[0,0,0,0,0,0,1,0],[1,0,0,0,0,0,0,0],
  [0,1,1,1,1,1,1,0],[0,0,0,0,0,0,-1,0],[0,0,0,0,0,-1,0,0],
  [0,0,0,0,-1,0,0,0],[0,0,0,-1,0,0,0,0],[0,0,-1,0,0,0,0,0],
  [0,0,0,0,0,0,0,1]]],
```

```
[[(1)*<<0,0,1,0,0,1,1,0>>+(1)*<<0,1,0,0,0,2,0,0>>+(-1)*<<0,0,0,0,0,1,0,2>>+(-1)*
<<0,0,0,0,0,0,0,3>>,(1)*<<0,0,1,0,0,0,2,0>>+(1)*<<0,1,0,0,0,1,1,0>>+(-1)*<<0,0,0
,0,0,1,2>>+(-1)*<<0,0,0,0,0,0,0,3>>,(1)*<<0,0,0,0,0,1,0,3>>+(-1)*<<0,0,0,0,0,0
,1,3>>],
 [(1)*<<0,0,1,0,0,1,1,0>>+(1)*<<0,1,0,0,0,2,0,0>>+(-1)*<<0,0,0,0,0,1,0,2>>,(1)*<
<0,0,1,0,0,0,2,0>>+(1)*<<0,1,0,0,0,1,1,0>>+(-1)*<<0,0,0,0,0,0,1,2>>+(-1)*<<0,0,0
,0,0,0,0,3>>,(1)*<<0,0,0,0,0,1,0,3>>]]]
```

Reference

sm1_reduction, sm1_rat_to_p

18.2.5 sm1_deRham

sm1_deRham([*f*, *v*]|proc=*p*)

:: ask the server to evaluate the dimensions of the de Rham cohomology groups of C^n - (the zero set of *f*=0).

return List

p Number

f String or polynomial

v List

- It returns the dimensions of the de Rham cohomology groups of X = C^n \ V(*f*). In other words, it returns [dim H^0(X,C), dim H^1(X,C), dim H^2(X,C), ..., dim H^n(X,C)].
- *v* is a list of variables. n = length(*v*).
- sm1_deRham requires huge computer resources. For example, sm1_deRham(0,[x*y*z*(x+y+z-1)*(x-y),[x,y,z]]) is already very hard.
- To efficiently analyze the roots of b-function, ox_asir should be used from ox_sm1_forAsir. It is recommended to load the communication module for ox_asir by the command
  sm1(0,"[(parse) (oxasir.sm1) pushfile] extension"); This command is automatically executed when ox_sm1_forAsir is started.
- If you make an interruption to the function sm1_deRham by ox_reset(Sm1_proc);, the server might get out of the standard mode. So, it is strongly recommended to execute the command ox_shutdown(Sm1_proc); to interrupt and restart the server.

```
[332] sm1_deRham([x^3-y^2,[x,y]]);
[1,1,0]
[333] sm1_deRham([x*(x-1),[x]]);
[1,2]
```

Reference

sm1_start, deRham (sm1 command)

Reference paper

Oaku, Takayama, An algorithm for de Rham cohomology groups of the complement of an affine variety via D-module computation, Journal of pure and applied algebra 139 (1999), 201–233.

18.2.6 sm1_hilbert

`sm1_hilbert([`*f*,*v*`]|proc=`*p*`)`
:: ask the server to compute the Hilbert polynomial for the set of polynomials *f*.

`hilbert_polynomial(`*f*,*v*`)`
:: ask the server to compute the Hilbert polynomial for the set of polynomials *f*.

return Polynomial

p Number

f, *v* List

- It returns the Hilbert polynomial h(k) of the set of polynomials *f* with respect to the set of variables *v*.
- h(k) = dim_Q F_k/I \cap F_k where F_k the set of polynomials of which degree is less than or equal to k and I is the ideal generated by the set of polynomials *f*.
- Note for sm1_hilbert: For an efficient computation, it is preferable that the set of polynomials *f* is a set of monomials. In fact, this function firstly compute a Grobner basis of *f*, and then compute the Hilbert polynomial of the initial monomials of the basis. If the input *f* is already a Grobner basis, a Grobner basis is recomputed in this function, which is a waste of time and Grobner basis computation in the ring of polynomials in `sm1` is slower than in `asir`.

```
[346] load("katsura")$
[351] A=hilbert_polynomial(katsura(5),[u0,u1,u2,u3,u4,u5]);
32

[279] load("katsura")$
[280] A=gr(katsura(5),[u0,u1,u2,u3,u4,u5],0)$
[281] dp_ord();
0
[282] B=map(dp_ht,map(dp_ptod,A,[u0,u1,u2,u3,u4,u5]));
[(1)*<<1,0,0,0,0,0>>,(1)*<<0,0,0,2,0,0>>,(1)*<<0,0,1,1,0,0>>,(1)*<<0,0,2,0,0,0>>,
 (1)*<<0,1,1,0,0,0>>,(1)*<<0,2,0,0,0,0>>,(1)*<<0,0,0,1,1,1>>,(1)*<<0,0,0,1,2,0>>,
 (1)*<<0,0,1,0,2,0>>,(1)*<<0,1,0,0,2,0>>,(1)*<<0,1,0,1,1,0>>,(1)*<<0,0,0,0,2,2>>,
  (1)*<<0,0,1,0,1,2>>,(1)*<<0,1,0,0,1,2>>,(1)*<<0,1,0,1,0,2>>,(1)*<<0,0,0,0,3,1>>,
  (1)*<<0,0,0,0,4,0>>,(1)*<<0,0,0,0,1,4>>,(1)*<<0,0,0,1,0,4>>,(1)*<<0,0,1,0,0,4>>,
 (1)*<<0,1,0,0,0,4>>,(1)*<<0,0,0,0,0,6>>]
[283] C=map(dp_dtop,B,[u0,u1,u2,u3,u4,u5]);
[u0,u3^2,u3*u2,u2^2,u2*u1,u1^2,u5*u4*u3,u4^2*u3,u4^2*u2,u4^2*u1,u4*u3*u1,
 u5^2*u4^2,u5^2*u4*u2,u5^2*u4*u1,u5^2*u3*u1,u5*u4^3,u4^4,u5^4*u4,u5^4*u3,
 u5^4*u2,u5^4*u1,u5^6]
[284] sm1_hilbert([C,[u0,u1,u2,u3,u4,u5]]);
32
```

Reference
: sm1_start, sm1_gb, longname

18.2.7 sm1_genericAnn

`sm1_genericAnn([`*f*,*v*`]|proc=`*p*`)`
:: It computes the annihilating ideal for *f*^s. *v* is the list of variables. Here, s is *v*[0] and *f* is a polynomial in the variables `rest(`*v*`)`.

return List

p Number

f Polynomial

v List

- This function computes the annihilating ideal for *f*^s. *v* is the list of variables. Here, s is *v*[0] and *f* is a polynomial in the variables `rest(`*v*`)`.

```
[595] sm1_genericAnn([x^3+y^3+z^3,[s,x,y,z]]);
[-x*dx-y*dy-z*dz+3*s,z^2*dy-y^2*dz,z^2*dx-x^2*dz,y^2*dx-x^2*dy]
```

`Reference`
`sm1_start`

18.2.8 sm1_wTensor0

`sm1_wTensor0([`*f*,*g*,*v*,*w*`]|proc=`*p*`)`
:: It computes the D-module theoretic 0-th tensor product of *f* and *g*.

return List

p Number

f, *g*, *v*, *w* List

- It returns the D-module theoretic 0-th tensor product of *f* and *g*.
- *v* is a list of variables. *w* is a list of weights. The integer *w*[i] is the weight of the variable *v*[i].
- `sm1_wTensor0` calls `wRestriction0` of `ox_sm1`, which requires a generic weight vector *w* to compute the restriction. If *w* is not generic, the computation fails.
- Let F and G be solutions of *f* and *g* respectively. Intuitively speaking, the 0-th tensor product is a system of differential equations which annihilates the function FG.
- The answer is a submodule of a free module D^r in general even if the inputs *f* and *g* are left ideals of D.

```
[258]  sm1_wTensor0([[x*dx -1, y*dy -4],[dx+dy,dx-dy^2],[x,y],[1,2]]);
[[-y*x*dx-y*x*dy+4*x+y],[5*x*dx^2+5*x*dx+2*y*dy^2+(-2*y-6)*dy+3],
 [-25*x*dx+(-5*y*x-2*y^2)*dy^2+((5*y+15)*x+2*y^2+16*y)*dy-20*x-8*y-15],
 [y^2*dy^2+(-y^2-8*y)*dy+4*y+20]]
```

18.2.9 sm1_reduction

`sm1_reduction([`*f*,*g*,*v*,*w*`]|proc=`*p*`)`
::

return List

f Polynomial

g, v, w List

p Number (the process number of ox_sm1)

- It reduces *f* by the set of polynomial *g* in the homogenized Weyl algebra; it applies the division algorithm to *f*. The set of variables is *v* and *w* is weight vectors to determine the order, which can be ommited. `sm1_reduction_noH` is for the Weyl algebra.
- The return value is of the form [r,c0,[c1,...,cm],[g1,...gm]] where *g*=[g1, ..., gm] and r/c0 + c1 g1 + ... + cm gm = 0. r/c0 is the normal form.
- The function reduction reduces reducible terms that appear in lower order terms.
- The functions sm1_reduction_d(P,F,G) and sm1_reduction_noH_d(P,F,G) are for distributed polynomials.

```
[259] sm1_reduction([x^2+y^2-4,[y^4-4*y^2+1,x+y^3-4*y],[x,y]]);
[x^2+y^2-4,1,[0,0],[x+y^3-4*y,y^4-4*y^2+1]]
[260] sm1_reduction([x^2+y^2-4,[y^4-4*y^2+1,x+y^3-4*y],[x,y],[[x,1]]]);
[0,1,[-y^2+4,-x+y^3-4*y],[x+y^3-4*y,y^4-4*y^2+1]]
```

Reference

`sm1_start`, `sm1_find_proc`, `d_true_nf`

18.2.10 sm1_xml_tree_to_prefix_string

`sm1_xml_tree_to_prefix_string(`*s*`|proc=`*p*`)`

:: Translate OpenMath Tree Expression *s* in XML to a prefix notation.

return String

p Number

s String

- It translate OpenMath Tree Expression *s* in XML to a prefix notation.
- This function should be moved to om_* in a future.
- `om_xml_to_cmo(OpenMath Tree Expression)` returns CMO_TREE. asir has not yet understood this CMO.
- `java` execution environment is required. (For example, `/usr/local/jdk1.1.8/bin` should be in the command search path.)

```
[263] load("om");
1
[270] F=om_xml(x^4-1);
control: wait OX
Trying to connect to the server... Done.
<OMOBJ><OMA><OMS name="plus" cd="basic"/><OMA>
<OMS name="times" cd="basic"/><OMA>
<OMS name="power" cd="basic"/><OMV name="x"/><OMI>4</OMI></OMA>
<OMI>1</OMI></OMA><OMA><OMS name="times" cd="basic"/><OMA>
<OMS name="power" cd="basic"/><OMV name="x"/><OMI>0</OMI></OMA>
<OMI>-1</OMI></OMA></OMA></OMOBJ>
[271] sm1_xml_tree_to_prefix_string(F);
basic_plus(basic_times(basic_power(x,4),1),basic_times(basic_power(x,0),-1))
```

`Reference`
`om_*`, `OpenXM/src/OpenMath`, `eval_str`

18.2.11 sm1_syz

`sm1_syz([`*f*, *v*, *w*`]|proc=`*p*`)`
:: computes the syzygy of *f* in the ring of differential operators with the variable *v*.

return List

p Number

f, *v*, *w* List

- The return values is of the form [s,[*g*, *m*, *t*]]. Here *s* is the syzygy of *f* in the ring of differential operators with the variable *v*. *g* is a Groebner basis of *f* with the weight vector *w*, and *m* is a matrix that translates the input matrix *f* to the Gr\"obner basis *g*. *t* is the syzygy of the Gr\"obner basis *g*. In summary, $g = m\ f$ and $s\ f = 0$ hold as matrices.
- The weight vectors are given by *w*, which can be omitted. If *w* is not given, the graded reverse lexicographic order will be used to compute Grobner basis.
- When a non-term order is given, the Grobner basis is computed in the homogenized Weyl algebra (See Section 1.2 of the book of SST). The homogenization variable h is automatically added.

```
[293] sm1_syz([[x*dx+y*dy-1,x*y*dx*dy-2],[x,y]]);
[[[y*x*dy*dx-2,-x*dx-y*dy+1]],    generators of the syzygy
 [[[x*dx+y*dy-1],[y^2*dy^2+2]],   grobner basis
  [[1,0],[y*dy,-1]],              transformation matrix
 [[y*x*dy*dx-2,-x*dx-y*dy+1]]]]
[294]sm1_syz([[x^2*dx^2+x*dx+y^2*dy^2+y*dy-4,x*y*dx*dy-1],[x,y],[[dx,-1,x,1]]]);
[[[y*x*dy*dx-1,-x^2*dx^2-x*dx-y^2*dy^2-y*dy+4]], generators of the syzygy
 [[[x^2*dx^2+h^2*x*dx+y^2*dy^2+h^2*y*dy-4*h^4],[y*x*dy*dx-h^4], GB
  [h^4*x*dx+y^3*dy^3+3*h^2*y^2*dy^2-3*h^4*y*dy]],
 [[1,0],[0,1],[y*dy,-x*dx]],     transformation matrix
 [[y*x*dy*dx-h^4,-x^2*dx^2-h^2*x*dx-y^2*dy^2-h^2*y*dy+4*h^4]]]]
```

18.2.12 sm1_mul

`sm1_mul(`*f*,*g*,*v*`|proc=`*p*`)`
:: ask the sm1 server to multiply *f* and *g* in the ring of differential operators over *v*.

return Polynomial or List

p Number

f, *g* Polynomial or List

v List

- Ask the sm1 server to multiply *f* and *g* in the ring of differential operators over *v*.

- `sm1_mul_h` is for homogenized Weyl algebra.

```
[277] sm1_mul(dx,x,[x]);
x*dx+1
[278] sm1_mul([x,y],[1,2],[x,y]);
x+2*y
[279] sm1_mul([[1,2],[3,4]],[[x,y],[1,2]],[x,y]);
[[x+2,y+4],[3*x+4,3*y+8]]
```

18.2.13 sm1_distraction

`sm1_distraction([`*f*,*v*,*x*,*d*,*s*`]|proc=`*p*`)`
:: ask the `sm1` server to compute the distraction of *f*.

return List

p Number

f Polynomial

v,*x*,*d*,*s* List

- It asks the `sm1` server of the descriptor number *p* to compute the distraction of *f* in the ring of differential operators with variables *v*.
- *x* is a list of x-variables and *d* is that of d-variables to be distracted. *s* is a list of variables to express the distracted *f*.
- Distraction is roughly speaking to replace x*dx by a single variable x. See Saito, Sturmfels, Takayama : Grobner Deformations of Hypergeometric Differential Equations at page 68 for details.

```
[280] sm1_distraction([x*dx,[x],[x],[dx],[x]]);
x
[281] sm1_distraction([dx^2,[x],[x],[dx],[x]]);
x^2-x
[282] sm1_distraction([x^2,[x],[x],[dx],[x]]);
x^2+3*x+2
[283] fctr(@);
[[1,1],[x+1,1],[x+2,1]]
[284] sm1_distraction([x*dx*y+x^2*dx^2*dy,[x,y],[x],[dx],[x]]);
(x^2-x)*dy+x*y
```

`Reference`
`distraction2(sm1),`

18.2.14 sm1_gkz

`sm1_gkz([`*A*,*B*`]|proc=`*p*`)`
:: Returns the GKZ system (A-hypergeometric system) associated to the matrix *A* with the parameter vector *B*.

return List

p Number

A, *B* List

- Returns the GKZ hypergeometric system (A-hypergeometric system) associated to the matrix

```
[280] sm1_gkz([  [[1,1,1,1],[0,1,3,4]],  [0,2] ]);
[[x4*dx4+x3*dx3+x2*dx2+x1*dx1,4*x4*dx4+3*x3*dx3+x2*dx2-2,
 -dx1*dx4+dx2*dx3,-dx2^2*dx4+dx1*dx3^2,dx1^2*dx3-dx2^3,-dx2*dx4^2+dx3^3],
 [x1,x2,x3,x4]]
```

18.2.15 sm1_appell1

`sm1_appell1(`*a*`|proc=`*p*`)`
:: Returns the Appell hypergeometric system F_1 or F_D.

return List

p Number

a List

- Returns the hypergeometric system for the Lauricella function F_D(a,b1,b2,...,bn,c;x1,...,xn) where a =(a,c,b1,...,bn). When n=2, the Lauricella function is called the Appell function F_1. The parameters a, c, b1, ..., bn may be rational numbers.

```
[281] sm1_appell1([1,2,3,4]);
[[((-x1+1)*x2*dx1-3*x2)*dx2+(-x1^2+x1)*dx1^2+(-5*x1+2)*dx1-3,
  (-x2^2+x2)*dx2^2+((-x1*x2+x1)*dx1-6*x2+2)*dx2-4*x1*dx1-4,
  ((-x2+x1)*dx1+3)*dx2-4*dx1],       equations
 [x1,x2]]                            the list of variables

[282] sm1_gb(@);
[[((-x2+x1)*dx1+3)*dx2-4*dx1,((-x1+1)*x2*dx1-3*x2)*dx2+(-x1^2+x1)*dx1^2
  +(-5*x1+2)*dx1-3,(-x2^2+x2)*dx2^2+((-x2^2+x1)*dx1-3*x2+2)*dx2
  +(-4*x2-4*x1)*dx1-4,
  (x2^3+(-x1-1)*x2^2+x1*x2)*dx2^2+((-x1*x2+x1^2)*dx1+6*x2^2
 +(-3*x1-2)*x2+2*x1)*dx2-4*x1^2*dx1+4*x2-4*x1],
 [x1*dx1*dx2,-x1^2*dx1^2,-x2^2*dx1*dx2,-x1*x2^2*dx2^2]]

[283] sm1_rank(sm1_appell1([1/2,3,5,-1/3]));
1

[285] Mu=2$ Beta = 1/3$
[287] sm1_rank(sm1_appell1([Mu+Beta,Mu+1,Beta,Beta,Beta]));
4
```

18.2.16 sm1_appell4

`sm1_appell4(`*a*`|proc=`*p*`)`
:: Returns the Appell hypergeometric system F_4 or F_C.

return List

p Number

a List

- Returns the hypergeometric system for the Lauricella function F_4(a,b,c1,c2,...,cn;x1,...,xn) where a =(a,b,c1,...,cn). When n=2, the Lauricella function is called the Appell function F_4. The parameters a, b, c1, ..., cn may be rational numbers.

```
[281] sm1_appell4([1,2,3,4]);
  [[-x2^2*dx2^2+(-2*x1*x2*dx1-4*x2)*dx2+(-x1^2+x1)*dx1^2+(-4*x1+3)*dx1-2,
  (-x2^2+x2)*dx2^2+(-2*x1*x2*dx1-4*x2+4)*dx2-x1^2*dx1^2-4*x1*dx1-2],
                                                          equations
    [x1,x2]]                                  the list of variables

[282] sm1_rank(@);
4
```

18.2.17 `sm1_rank`

`sm1_rank(`*a*`|proc=`*p*`)`
:: Returns the holonomic rank of the system of differential equations a.

return Number

p Number

a List

- It evaluates the dimension of the space of holomorphic solutions at a generic point of the system of differential equations a. The dimension is called the holonomic rank.
- *a* is a list consisting of a list of differential equations and a list of variables.
- `sm1_rrank` returns the holonomic rank when a is regular holonomic. It is generally faster than `sm1_rank`.

```
[284]  sm1_gkz([  [[1,1,1,1],[0,1,3,4]],  [0,2] ]);
[[x4*dx4+x3*dx3+x2*dx2+x1*dx1,4*x4*dx4+3*x3*dx3+x2*dx2-2,
  -dx1*dx4+dx2*dx3, -dx2^2*dx4+dx1*dx3^2,dx1^2*dx3-dx2^3,-dx2*dx4^2+dx3^3],
 [x1,x2,x3,x4]]
[285] sm1_rrank(@);
4

[286]  sm1_gkz([  [[1,1,1,1],[0,1,3,4]],  [1,2]]);
[[x4*dx4+x3*dx3+x2*dx2+x1*dx1-1,4*x4*dx4+3*x3*dx3+x2*dx2-2,
 -dx1*dx4+dx2*dx3,-dx2^2*dx4+dx1*dx3^2,dx1^2*dx3-dx2^3,-dx2*dx4^2+dx3^3],
 [x1,x2,x3,x4]]
[287] sm1_rrank(@);
```

```
5
```

18.2.18 sm1_auto_reduce

`sm1_auto_reduce(`*s*`|proc=`*p*`)`
:: Set the flag "AutoReduce" to *s*.

return Number

p Number

s Number

- If *s* is 1, then all Grobner bases to be computed will be the reduced Grobner bases.
- If *s* is 0, then Grobner bases are not necessarily the reduced Grobner bases. This is the default.

18.2.19 sm1_slope

`sm1_slope(`*ii*`,`*v*`,`*f_filtration*`,`*v_filtration*`|proc=`*p*`)`
:: Returns the slopes of differential equations *ii*.

return List

p Number

ii List (equations)

v List (variables)

f_filtration List (weight vector)

v_filtration
List (weight vector)

- `sm1_slope` returns the (geometric) slopes of the system of differential equations *ii* along the hyperplane specified by the V filtration *v_filtration*.
- *v* is a list of variables.
- As to the algorithm, see "A.Assi, F.J.Castro-Jimenez and J.M.Granger, How to calculate the slopes of a D-module, Compositio Math, 104, 1-17, 1996" Note that the signs of the slopes are negative, but the absolute values of the slopes are returned.
- The return value is a list of lists. The first entry of each list is the slope and the second entry is the weight vector for which the microcharacteristic variety is not bihomogeneous.

```
[284] A= sm1_gkz([  [[1,2,3]],  [-3] ]);


[285] sm1_slope(A[0],A[1],[0,0,0,1,1,1],[0,0,-1,0,0,1]);

[286] A2 = sm1_gkz([ [[1,1,1,0],[2,-3,1,-3]], [1,0]]);
     (* This is an interesting example given by Laura Matusevich,
```

```
            June 9, 2001 *)

     [287] sm1_slope(A2[0],A2[1],[0,0,0,0,1,1,1,1],[0,0,0,-1,0,0,0,1]);
```

Reference

sm_gb

19 DSOLV Functions

This section is a collection of functions to solve regular holonomic systems in terms of series. Algorithms are explained in the book [SST]. You can load this package by the command `load("dsolv");` This package requires `Diff` and `dmodule`.

This package uses `ox_sm1`, so the variables you can use is as same as those you can use in the package `sm1`.

19.1 Functions

19.1.1 dsolv_dual

`dsolv_dual(`*f*, *v*`)`
:: Grobner dual of *f*.

return List

f, *v* List

- It returns the Grobner dual of *f* in the ring of polynomials with variables *v*.
- The ideal generated by *f* must be primary to the maximal ideal generated by *v*. If it is not primary to the maximal ideal, then this function falls into an infinite loop.
- This is an implementation of Algorithm 2.3.14 of the book [SST]. If we replace variables x, y, ... in the output by log(x), log(y), ..., then these polynomials in log are solutions of the system of differential equations *f*`_(x->x*dx, y->y*dy, ...)`.

```
[435] dsolv_dual([y-x^2,y+x^2],[x,y]);
[x,1]
[436] dsolv_act(y*dy-sm1_mul(x*dx,x*dx,[x,y]),log(x),[x,y]);
0
[437] dsolv_act(y*dy+sm1_mul(x*dx,x*dx,[x,y]),log(x),[x,y]);
0

[439] primadec([y^2-x^3,x^2*y^2],[x,y]);
[[[y^2-x^3,y^4,x^2*y^2],[y,x]]]
[440] dsolv_dual([y^2-x^3,x^2*y^2],[x,y]);
[x*y^3+1/4*x^4*y, x^2*y, x*y^2+1/12*x^4, y^3+x^3*y,
 x^2, x*y, y^2+1/3*x^3, x, y, 1]

[441] dsolv_test_dual();
  Output is  omitted.
```

19.1.2 dsolv_starting_term

`dsolv_starting_term(`*f*, *v*, *w*`)`
:: Find the starting term of the solutions of the regular holonomic system *f* to the direction *w*.

return List

f, v, w List

- Find the starting term of the solutions of the regular holonomic system *f* to the direction *w*.
- The return value is of the form [[*e1*, *e2*, ...], [*s1*, *s2*, ...]] where *e1* is an exponent vector and *s1* is the corresponding solution set, and so on.
- If you set `Dsolv_message_starting_term` to 1, then this function outputs messages during the computation.

```
[1076]   F = sm1_gkz( [ [[1,1,1,1,1],[1,1,0,-1,0],[0,1,1,-1,0]], [1,0,0]]);
[[x5*dx5+x4*dx4+x3*dx3+x2*dx2+x1*dx1-1,-x4*dx4+x2*dx2+x1*dx1,
  -x4*dx4+x3*dx3+x2*dx2,
  -dx2*dx5+dx1*dx3,dx5^2-dx2*dx4],[x1,x2,x3,x4,x5]]
[1077]  A= dsolv_starting_term(F[0],F[1],[1,1,1,1,0])$
Computing the initial ideal.
Done.
Computing a primary ideal decomposition.
Primary ideal decomposition of the initial Frobenius ideal
to the direction [1,1,1,1,0] is
[[[x5+2*x4+x3-1,x5+3*x4-x2-1,x5+2*x4+x1-1,3*x5^2+(8*x4-6)*x5-8*x4+3,
   x5^2-2*x5-8*x4^2+1,x5^3-3*x5^2+3*x5-1],
 [x5-1,x4,x3,x2,x1]]]

---------- root is [ 0 0 0 0 1 ]
---------- dual system is
[x5^2+(-3/4*x4-1/2*x3-1/4*x2-1/2*x1)*x5+1/8*x4^2
 +(1/4*x3+1/4*x1)*x4+1/4*x2*x3-1/8*x2^2+1/4*x1*x2,
 x4-2*x3+3*x2-2*x1,x5-x3+x2-x1,1]

[1078] A[0];
[[ 0 0 0 0 1 ]]
[1079] map(fctr,A[1][0]);
[[[1/8,1],[x5,1],[log(x2)+log(x4)-2*log(x5),1],
          [2*log(x1)-log(x2)+2*log(x3)+log(x4)-4*log(x5),1]],
 [[1,1],[x5,1],[-2*log(x1)+3*log(x2)-2*log(x3)+log(x4),1]],
 [[1,1],[x5,1],[-log(x1)+log(x2)-log(x3)+log(x5),1]],
 [[1,1],[x5,1]]]
```

20 TIGERS Functions

This chapter describes interface functions for tigers ox server `ox_sm1_tigers`.

20.0.1 `tigers`

`tigers(a|proc=a)`
:: It asks the `tigers` server of the descriptor number p to enumerate all Grobner bases associated to the toric variaty defined by the matrix a.

return List

p Number

a List

- It asks the `tigers` server of the descriptor number p to enumerate all Grobner bases associated to the toric variaty defined by the matrix a.
- The system tigers is an expert system to enumerate all Gr\"obner bases of affine toric ideals. In other words, it can be used to determine the state polytope of a given affine toric ideal. As to a theoretical background, see the book
  B.Sturmfels, Grobner bases and Convex Polytopes.
  The original tigers is written by Birk Hubert. The algorithm used in explained in the paper
  B.Huber and R.Thomas, Computing Grobner Fans of Toric Ideals.

```
[395] A=[[1,1,1,1],[0,1,2,3]]$
[306] S=tigers(A)$
[307] length(S);
8
[308] S[0];
[[[1,0,1,0],[0,2,0,0]],[[1,0,0,1],[0,1,1,0]],[[0,1,0,1],[0,0,2,0]]]
[309] S[1];
[[[1,0,0,1],[0,1,1,0]],[[0,2,0,0],[1,0,1,0]],[[0,1,0,1],[0,0,2,0]]]
```

In this example, all reduced Grobner bases for the toric ideal associated to the matrix A are stored in S. There are eight distinct Grobner bases of A. [[i_1, i_2, ...],[j_1, j_2, ...]] is a set of exponents of two monomials and stands for a binomial. For example, the S[0] consists of
x1 x3 - x2^2, x1 x4 - x2 x3, x2 x4 - x3^2.
<x1 x3, x1 x4, x2 x4> is the initial ideal of S[0].

Index

(Index is nonexistent)

(Index is nonexistent)

Short Contents

1 Introduction 1
2 Function Names in Asir Contrib 2
3 Numbers (Standard Mathematical Functions) 3
4 Calculus (Standard Mathematical Functions) 4
5 Series (Standard Mathematical Functions) 5
6 Hypergeometric Functions (Standard Mathematical Functions) 6
7 Matrix (Standard Mathematical Functions) 7
8 Graphic (Standard Mathematical Functions) 8
9 Print (Standard Mathematical Functions) 9
10 Polynomials (Standard Mathematical Functions) 10
11 Complex (Standard Mathematical Functions) 11
12 OpenMath Function Names 12
13 OpenXM-Contrib General Functions 14
14 GNUPLOT Functions 15
15 Mathematica Functions 19
16 OpenMath Functions 22
17 PHC Functions 24
18 SM1 Functions 26
19 DSOLV Functions 40
20 TIGERS Functions 42
Index 43

Table of Contents

1 Introduction 1

2 Function Names in Asir Contrib 2

3 Numbers (Standard Mathematical Functions) 3

4 Calculus (Standard Mathematical Functions) 4

5 Series (Standard Mathematical Functions) . . . 5

6 Hypergeometric Functions (Standard Mathematical Functions) 6

7 Matrix (Standard Mathematical Functions) . . 7

8 Graphic (Standard Mathematical Functions) 8

9 Print (Standard Mathematical Functions) . . . 9

10 Polynomials (Standard Mathematical Functions) 10

11 Complex (Standard Mathematical Functions) 11

12 OpenMath Function Names 12

12.0.1 `OpenMath` CD Basic 12

13 OpenXM-Contrib General Functions 14

13.1 Functions 14

13.1.1 `ox_check_errors2` 14

14 GNUPLOT Functions 15

14.1 Functions 15
- 14.1.1 `gnuplot_start` 15
- 14.1.2 `gnuplot` 16
- 14.1.3 `gnuplot_plot_dots` 16
- 14.1.4 `gnuplot_output` 17
- 14.1.5 `gnuplot_plot_function` 18

15 Mathematica Functions 19

15.1 Functions 19
- 15.1.1 `m_start` 19
- 15.1.2 `m_tree_to_string` 20
- 15.1.3 `m_rtostr` 20

16 OpenMath Functions 22

- 16.0.1 `om_start` 22
- 16.0.2 `om_xml` 22
- 16.0.3 `om_xml_to_cmo` 23

17 PHC Functions 24

17.1 Functions 24
- 17.1.1 `phc_start` 24
- 17.1.2 `phc` 25

18 SM1 Functions 26

18.1 `ox_sm1_forAsir` Server 26
- 18.1.1 `ox_sm1_forAsir` 26

18.2 Functions 27
- 18.2.1 `sm1_start` 27
- 18.2.2 `sm1` 27
- 18.2.3 `sm1_push_int0` 28
- 18.2.4 `sm1_gb` 28
- 18.2.5 `sm1_deRham` 30
- 18.2.6 `sm1_hilbert` 31
- 18.2.7 `sm1_genericAnn` 32
- 18.2.8 `sm1_wTensor0` 32
- 18.2.9 `sm1_reduction` 32
- 18.2.10 `sm1_xml_tree_to_prefix_string` 33
- 18.2.11 `sm1_syz` 34
- 18.2.12 `sm1_mul` 34
- 18.2.13 `sm1_distraction` 35
- 18.2.14 `sm1_gkz` 35
- 18.2.15 `sm1_appell1` 36
- 18.2.16 `sm1_appell4` 36
- 18.2.17 `sm1_rank` 37
- 18.2.18 `sm1_auto_reduce` 38
- 18.2.19 `sm1_slope` 38

19 DSOLV Functions 40

19.1 Functions 40

19.1.1 `dsolv_dual` 40

19.1.2 `dsolv_starting_term` 40

20 TIGERS Functions 42

20.0.1 `tigers` 42

Index 43